## NOTICE OF PRODUCT CERTIFICATION



To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

Series " 4-9/16""
20 Minute Category C
<b>Proprietary PVC Door Frame</b>
Manufacture Specific Fire Door Frames for Single Swing Installation in 20 Minute Locations
1/2" Minimum Latch Throw Single Swing Only
Maximum Size: 952mm x 2438mm Minimum Thickness: 116mm

## **SPECIFICATION**

NFPA 252 (2012) UL 10(b) (2009) UBC Standard 7-2 (1997) UL 10(c) (2009) **PRODUCT RATING** 

20 Minute-Positive Pressure 20 Minute-Neutral Pressure Without Hose Stream Category C- Proprietary Frame

## **TEST REPORT**

Intertek Test Report No: 170410011SHF-BP-1

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC. 4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124/ Fax: (804) 684-5122